

Acid Stain WB 501 System

SYSTEM DATASHEET

SYSTEM DESCRIPTION

Acid Stain WB 501 is an acidic coloring solution which chemically reacts with concrete and other cementitious substrates to create translucent and variegated color effects. This system is sealed with low odor high performance waterborne epoxy and polyurethane coatings, giving it exceptional durability. The coloration becomes a permanent part of the substrate and cannot crack or peel. Acid Stain WB 501 gives a unique look that cannot be achieved with conventional polymer and pigment type stains. The material reacts individually with each substrate depending upon its available cement content, age, and porosity. Considerable variations in color and tone normally result from the use of Acid Stain WB 501, and many special color effects can be achieved using different methods of application.

FEATURES & BENEFITS

- Chemical resistant
- Abrasion resistant
- Impact resistant
- Low VOC formulation
- Qualifies for LEED projects
- Available in a satin finish
- Exceptional durability

PRODUCTS

- Acid Stain
- SK-E200
- SK-P501

SYSTEM USES

Acid Stain WB 501 System is designed for interior, conventional and architectural concrete.

COLORS

Available in 10 standard colors.

PHYSICAL PROPERTIES

Gloss (60 degrees):	90
Gloss (Satin material, 60 degrees)	50-60
Pendulum hardness, sec ASTM D 4336	175
Flexibility ASTM D 222	Passes 1/8 inch
Impact resistance ASTM D 2794	Passes 3/8 inch-pounds direct impact
Tabor abrasion (1000 gm. Load, 1000 cycles, CS 17 wheel)	32 mg. loss
Adhesion to concrete ASTM D 451	Concrete fails before loss of bond
Volatile Organic Compounds	100 grams/liter

SURFACE PREPARATION

Surface must be clean, dry and profiled prior to installation. Acceptable methods for preparation are diamond grinding or acid etching. If acid etching, follow APF written instructions. Concrete must have a minimum surface profile ICRI CSP 2, or a texture similar to 120 grit sand paper.

CHEMICAL RESISTANCE

Please refer to the Arizona Polymer Flooring Chemical Resistance Guide for full system chemical resistance.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc
4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921
623.435.2277 Tel. / 623.435.8585 Fax
www.super-krete.com



Acid Stain WB 501 System

SYSTEM DATASHEET

INSTALLATION

Please refer to the "Acid Stain WB 501 System Application Instructions" for information on installing this system.

MOISTURE VAPOR EMISSIONS PRECAUTIONS:

All concrete floors not poured over an effective moisture vapor retarder are subject to possible moisture vapor transmission that may lead to blistering and failure of the coating system. It is the coating applicator's responsibility to conduct calcium chloride testing in compliance with ASTM F1869, or relative humidity probe testing in compliance with ASTM-F2170, to determine if excessive levels of vapor emissions are present before applying any coatings. Arizona Polymer Flooring offers **S-1300 Pene-Krete®** for cementitious overlay products and **VaporSolve® Moisture Remediation** systems for resinous floor coatings. Consult our technical service department. Arizona Polymer Flooring and its sales agents will not be responsible for coating failures due to undetected moisture vapor emissions.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc

4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921

623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

